

Robimat X series Outdoor Robimat XL



Robimat X series Outdoor

Robimat XL



Introduction

- Protection class: IP24
- Winter resistant up to -20°C
- Version for locations exposed to vandalism
- Anti-vandalism panel
- Rain shield and weatherproof protection
- Coin insert slide and coin return drum
- Reinforced locking lever protection
- Security frame with side lock
- Laminated safety glass panel with UV filter
- Residual current circuit breaker
- High performance chiller unit with heater with "frost monitoring function", so that the internal temperature is held above 0°C
- Rear panel offers advertising opportunity



Overview

Dimensions: 1,856 x 1,178 x 1,210 mm (height x width x depth)*

Weight: approx. 459 kg (without products, depending on the layout)

Electrical connection values: 220 - 230 V / 50 Hz / min. 10 A

Power consumption: 750 W Protection class: IP24

*Deviations in the housing dimensions are possible due to add-on parts and accessories.

Design variants

Operator panel

■ RO = Operator panel RAL painted

Cabinet colors

■ Pure white (RAL 9010)

Robimat X series Outdoor Robimat XL



- White aluminum (RAL 9006)
- Jet black (RAL 9005)

An overview of the benefits:

- Anti-vandalism panel
- Rain shield and weatherproof protection
- Coin insert slide and coin return drum
- Reinforced locking lever protection
- Security frame with side lock
- Laminated safety glass panel with UV filter
- Residual current circuit breaker
- High performance chiller unit with heater with "frost monitoring function", so that the internal temperature is held above 0°C
- Rear panel offers advertising opportunity
- KESO

Optional

■ Impact protection made of 8 mm thick laminated safety glass instead of 12mm PC



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



